

DECLARATION OF PERFORMANCES

WPBSP096

1. Number and/or identification code:

WPBSP096

2. Name, type, batch or serial number:

MOPLY N PLUS FP 3 KG

3. Intended uses:

Reinforced bitumen sheets for roof waterproofing

4. Name and conctact adress of the manufacturer:

TEXSA SYSTEMS SLU - C/ Ferro, 7 - Pol. Can Pelegrí - 08755 Castellbisbal - Barcelona (SPAIN)

5. System or systems of assessment and verification of constancy of performance:

System 2+

6. Name and identification number of the notified body and tasks:

Task carried out:	System	Done / Issued:
Factory Production Control (FPC)	2+	AENOR - 0099
	on the basis of: 0099/CPR/A85/0087	
Fire reaction	3	APPLUS-LGAI
External fire behaviour	3	APPLUS-LGAI

7. Declared performance

Essential characteristics	Performance		Harmonised technical specification
External fire behaviour	Broof(t1)		_
Fire reaction	E		
Watertightness	Pass (10 kPa)		
Tensile properties:			1
Maximum tensile strength (L x T) (N/50mm)	600 ± 200	400 ± 150	EN 13707:2005+A2:2010
Elongation (L x T) (%)	45 ± 15	45 ± 15	
Root penetration resistance	NE		EN 13707:2005+A2:2010
Static load resistance (kg)	≥ 15		
Impact resistance (mm)	≥ 1000		
Tear strength (nail) (L x T) (N)	NE		
Durability (flexibility / flow resistance)	NE		
Flexibility at low temperature (°C)	≤ -10		

NE - Not relevant, NPD - No performance determined

The performance of the product identified in points 1 is in conformity with the declared performace in point 6.

This declaration of performance is issued under the sole reponsability of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:



J. Fiter RD& i Director