

BARRA PERFORADA DE CHAPA GALVANIZADA

The PERFORATED ZINC-PLATED BAR is a sheet of galvanized steel with perforated holes every 25 mm.

ADVANTAGES

- Easy to install
- Light

APPLICATION

The PERFORATED ZINC-PLATED BAR is used for mechanically affixing PVC and TPO waterproofing membranes, used as a fixing element around the perimeter of the roof.

Synthetic Waterproofing PVC

TEXSA SYSTEMS SLU reserves the right to modify the information contained herein without prior notice and declines all liability in cases of errors produced due to inappropriate use of the product. The values shown in the technical sheet are the mean values from tests in our lab.

TEXSA SYSTEMS SLU. c/ Ferro 7, Pol. Ind. Can Pelegrí 08755 Castellbisbal-Barcelona (+34) 93 635 14 00



INSTALLATION

PERFORATED ZINC-PLATED BARS are placed on top of the waterproofing membrane and attached with specific fixings below all vertical elements. By using the bar, the load is uniformly distributed.

For use with the perforated bar:

 $\bullet\,$ FLAGOFIL cable: must be placed and welded to the membrane with hot air.

• FINAL PROTECTIVE SHEET: to protect against perforations at the edge of the sheet.

Synthetic Waterproofing PVC

TEXSA SYSTEMS SLU reserves the right to modify the information contained herein without prior notice and declines all liability in cases of errors produced due to inappropriate use of the product. The values shown in the technical sheet are the mean values from tests in our lab.

TEXSA SYSTEMS SLU. c/ Ferro 7, Pol. Ind. Can Pelegrí 08755 Castellbisbal-Barcelona (+34) 93 635 14 00